

selectable Gallonage nozzles

Style 360, 361, 362

- Combination pattern nozzles with versatile multiple flow settings.
- Produces straight stream for maximum reach and superb wide fog pattern for optimal firefighting protection.
- Available in either lightweight hard coat anodized aluminium or corrosion resistant brass construction.
- Available in tip only and shutoff combinations.
- Standard operating pressure at 100 psi (7 bar), optional; 85 psi (6 bar) or 75 psi (5 bar).
- style 360 and 362 can be used for high pressure applications up to 580 psi (40 bar) hydrostatic pressure.
- Minimal maintenance reflected in robust design, precision machining and quality materials.
- Standard NH inlet or optional BIM / Machino / Storz inlet
- Optional 1-1/2" inlet size.
- Compatible with Foam Tubes Style 210.
- Conforms to all aspects of NFPA 1964 (Spray Nozzles, Shutoff and Tips).



Specifications

Style	Inlet Size	Length	Weigth Lbs(kg)	Flow Settings	
				GPM	LPM
360	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	5-10-24-40	19-37-90-150
361	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	13-25-40-60	50-100-150-230
362	1"(25mm)	7.4"(190mm)	2.3(1.1kg)	12-23-30	50-90-115

selectable Gallonage nozzles

Unique Features On Protek Nozzles

